

# AWS S3

2.0.0 部署AWS S3 minio 部署AWS S3

## config.php


config.php S3

```
$config['s3']['region'] = 'us-east-1';
$config['s3']['endpoint'] = 'http://minio.xxx.com:9000';
$config['s3']['key'] = 'xxx';
$config['s3']['secret'] = 'xxx';
$config['s3']['bucket'] = 'xxx';
```

- region
- endpointS3 http://xxx.com:9000
- key:minio
- bucket



- / S3S3



本地 Backblaze B2 FTP 腾讯COS 七牛云 S3

绑定域名 https://v.bmp.ovh/


权重 0

游客上传 ☐ 是 ☒ 否

开关 ☐


保存

S3“”S3



- `$config['s3']['region']` `cn-south-1`
- `$config['s3']['endpoint']` `Endpoint https / https://s3-cn-south-1.qiniucs.com`

<https://portal.giniu.com/user/key> AccessKey/SecretKey

- `$config['s3']['key']` AccessKey
- `$config['s3']['bucket']` 



```
$config['s3']['region'] = 'us-east-1';
$config['s3']['endpoint'] = 'http://minio.xxx.com:9000';
$config['s3']['key'] = 'xxx';
```

```
$config['s3']['secret'] = 'xxx';
$config['s3']['bucket'] = 'xxx';
```

## 配置OSS Region和Endpoint

- region 配置Region ID
- endpoint http://bucket. 配置Endpoint http://bucket.oss-cn-hangzhou.aliyuncs.com
- bucket 配置Bucket名称

## 配置AccessKey ID和AccessKey Secret

- key 配置AccessKey ID
- secret 配置AccessKey Secret

配置完成

```
$config['s3']['region'] = 'oss-ap-southeast-1';
$config['s3']['endpoint'] = 'http://bucket.oss-ap-southeast-1.aliyuncs.com';
$config['s3']['key'] = 'xxx';
$config['s3']['secret'] = 'xxx';
$config['s3']['bucket'] = 'bucket';
```

# Backblaze B2

Backblaze <https://www.backblaze.com/> 1TB 5\$/月

B2 - 配置

- 创建Bucket
- 创建Application Key
- 配置Bucket



配置 - 配置



{"cache-control": "max-age=604800"} 配置/配置



## #9

xiaoz 31 2022 07:39:28

xiaoz 17 2022 13:53:52