



data/config.php data/config.php



Nginx

```
#
location ~* ^/(class|controller|db|data|functions|templates)/.*.(db3|php|php5|sql)$ {
    return 403;
}
location ~* ^/(data)/.*.(html)$ {
    deny all;
}
location /db {
    deny all;
}

#
rewrite ^/click/(.*) /index.php?c=click&id=$1 break;
rewrite ^/api/(.*)?(.*) /index.php?c=api&method=$1&$2 break;
rewrite /login /index.php?c=login break;
```

- Ap.htaccess
- Docker
-

Nginx

1. Docker 2

- 1. http://IP
- 2. Nginx

Nginx

```
server {  
    listen 80;  
  
    #  
    server_name demo.onenav.top;  
  
    #  
    #access_log /data/logs/demo.onenav.top_nginx.log xlog;  
    charset utf-8,gbk;  
  
    location / {  
        proxy_connect_timeout 10;  
        # Default is HTTP/1, keepalive is only enabled in HTTP/1.1  
        proxy_http_version 1.1;  
        proxy_set_header Connection "";  
        #chunked_transfer_encoding off;  
        proxy_set_header Host $host;  
        #3080  
        proxy_pass http://127.0.0.1:3080;  
        proxy_set_header X-Real-IP $remote_addr;  
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
    }  
}
```