

# Nginx配置

## Nginx配置

配置NginxZdir

```
server {  
    listen 80;  
    #domain.com  
    server_name domain.com;  
  
    #  
  
    location = / {  
        proxy_pass http://127.0.0.1:6080;  
        proxy_set_header X-Real-IP $remote_addr;  
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
    }  
    # Vue, public  
    location ~* /(assets|public|api|admin) {  
        #Expires  
        if ( $uri ~* .*\. (gif|jpg|jpeg|png|bmp|webp|swf|flv|mp4|ts|ico|js|css|svg|ico)$ ) {  
            expires 7d;  
        }  
        client_max_body_size 1024m;  
        proxy_pass http://127.0.0.1:6080;  
        proxy_set_header X-Real-IP $remote_addr;  
        proxy_set_header Host $host;  
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
    }  
    # / assets/public/ , ,  
    location / {  
        rewrite ^/(.*) /public/$1;  
    }  
}
```

```
}
```

```
data/config/config.ini public_domain http://domain.com / http https
```

# Nginx

Nginx - -

image not found or type unknown



-

image not found or type unknown



```
# =
location = / {
    proxy_pass http://127.0.0.1:6080;
    proxy_set_header X-Real-IP $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
}
# Vue, public
location ~* /(assets|public|api|admin) {
    #Expires
    if ( $uri ~* \.(gif|jpg|jpeg|png|bmp|webp|swf|flv|mp4|ts|ico|js|css|svg|ico)$ ) {
        expires 7d;
    }
    proxy_pass http://127.0.0.1:6080;
    proxy_set_header X-Real-IP $remote_addr;
    proxy_set_header Host $host;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
}
# / /assets/public/ , ,
location / {
    rewrite ^/(.*) /public/$1;
}
```



image not found or type unknown

---

### #8

xiaoz ### 17 2022 07:45:07

xiaoz ### 12 2023 13:54:54